

01x MTP . 01x MXC PLUG 48F OM3 RIBBON

Basic characteristics

- ▲ Hermaphroditic PRIZM MT ferule
- ▲ Debris insensitivity of MXC plug connector



Benefits

- ▲ High density parallel connector
- ▲ Debris insensitivity of MXC plug connector

Applications

- ▲ Supercomputing
- ▲ Data Networking
- ▲ SAN

Temperature range

Controlled environment (-10°C/+60°C)

Cable parameters

Jacket material	N/A	
Cable construction	Bare ribbon	
Outer diameter	approx. 3,2mm x 0,35mm	
Fiber count	4x12	
Fiber type	MMF OM3	
Temperature range	operation:	-20°C to +70°C
	storage:	-20°C to +55°C
	installation:	-20°C to +55°C

01x MTP . 01x MXC PLUG 48F OM3 RIBBON

Connector parameters

	MTP	MXC
Compliance	US CONEC standard	US CONEC standard
Colour of housing	Aqua	Aqua
Colour of boot	Black	Black
Polish	Flat (PC)	N/A
Insertion Loss (@850nm)	<0,6dB	<1,2dB
Return Loss (@850nm)	>20dB	>20dB

Identification

Marking sleeve with unique serial number.

Packaging

Each assembly in sealed PE bag, bulk pack in cardboard box.

MXC, PRIZM MT and MTP is a registered trademark of US Conec, Ltd.

* Specifications are subject to change without notice

For more information contact our sales team at sales@sylex.sk