

01x MXC PLUG - 01x MXC PLUG 16F OM3 ROUND TRUNK

Basic characteristics

- ▲ Hermaphroditic PRIZM MT ferule
- ▲ Debris insensitivity of MXC plug connector



Benefits

- ▲ High density parallel connector
- ▲ Debris insensitivity of MXC plug connector

Applications

- ▲ Supercomputing
- ▲ Data Networking
- ▲ SAN

Temperature range

Controlled environment (-10°C/+60°C)

Cable parameters

Jacket material		LSZH
Cable construction		Round cable
Outer diameter		3,8mm
Fiber count		16
Fiber type		MMF OM3
Temperature range	operation:	-10°C to +70°C
	storage:	-25°C to +70°C
	installation:	-5°C to +50°C

01x MXC PLUG - 01x MXC PLUG 16F OM3 ROUND TRUNK

Connector parameters

	MXC
Compliance	US CONEC standard
Colour of housing	Aqua
Colour of boot	Black
Polish	N/A
Insertion Loss (@850nm)	<1,2dB
Return Loss (@850nm)	>20dB

Identification

Marking sleeve with unique serial number.

Packaging

Each assembly in sealed PE bag, bulk pack in cardboard box.

MXC and PRIZM MT is a registered trademark of US Conec, Ltd.

* Specifications are subject to change without notice

For more information contact our sales team at sales@sylex.sk